

PRODUCT NAME:	ACTIVE
USAGE:	MULTISPORT
MATERIAL:	PILE: PE monofilament (straight + texturized)
	PRIMARY BACKING: 100 % PP
	SECONDARY BACKING: SBR Latex
GAUGE:	3/8"
COLOUR:	bicolour green

PROPERTIES	UNIT	TYPICAL VALUE	TOLERANCE
Pile fineness - <i>straight</i>	[dtex]	8.000/4	± 10 %
Pile width	[mm]	1,1	± 10 %
Pile thickness	[µm]	300	± 10 %
Pile fineness - <i>texturized</i>	[dtex]	11.500/8	± 10 %
Pile width	[mm]	1	± 10 %
Pile thickness	[µm]	180	± 10 %
Pile weight per unit area	[g/m ²]	2.920	± 10 %
Stitch rate per 10 cm (length)	[-/10 cm]	20	± 10 %
Number of tufts/m ²	[-/m ²]	20.997	± 10 %
Number of piles/m ²	[-/m ²]	503.928	± 10 %
Pile height	[mm]	30	± 5 %
Weight primary backing	[g/m ²]	260	± 10 %
Weight secondary backing	[g/m ²]	950	± 10 %
Total weight	[g/m ²]	4.130	± 10 %
Turf withdrawal force	[N]	> 30	
Water permeability	[mm/h]	> 500	
UV stabilisation (QUV – lamp A)	[h]	5.000	
Colour fastness – grey scale	Scale	≥ 4	
Standard roll width	[m]	4,02	± 0,02

COMMENTS:

Product certificates: EN 15330-1; NF P90-112; DIN EN 13501-1; DIN 4102-1

Recommended infill:

- infill depth depending on type of shockpad and infill:
 - quartz sand 0,3 – 1,2 mm -> 10 mm (± 15 kg/m²)
- For the recommended amount of infill used for certified field, please see the laboratory test report.

In case of free installation without mechanical fixing or bonding the turf may shrink up to 1 % due to climatic changes.

The product must be installed in compliance with the JUTAgass® Installation Guide.

According to the Regulation (EC) No 1907/2006 (REACH), this product does not contain any dangerous substances.