

PRODUCT NAME:	PADEL MFT 12		
USAGE:	TENNIS, PADEL		
MATERIAL:	PILE:	PE monofilament (texturized)	
	PRIMARY BACKING:	100 % PP	
	SECONDARY BACKING:	SBR Latex	
GAUGE:	3/16"		
COLOUR:	bicolor green, blue, white, terracotta		

PROPERTIES	UNIT	TYPICAL VALUE	TOLERANCE
Pile fineness	[dtex]	8.800/8	± 10 %
Pile width	[mm]	0,9	± 10 %
Pile thickness	[µm]	170	± 10 %
Pile weight per unit area	[g/m ²]	1.353	± 10 %
Stitch rate per 10 cm (length)	[-/10 cm]	24	± 10 %
Number of tufts/m ²	[-/m ²]	50.394	± 10 %
Number of piles/m ²	[-/m ²]	806.304	± 10 %
Pile height	[mm]	12	± 5 %
Weight primary backing	[g/m ²]	201	± 10 %
Weight secondary backing	[g/m ²]	950	± 10 %
Total weight	[g/m ²]	2.504	± 10 %
Turf withdrawal force	[N]	> 30	
Water permeability	[mm/h]	> 500	
UV stabilisation (QUV – lamp A)	[h]	5.000	
Colour fastness – grey scale	Scale	≥ 4	
Standard roll width	[m]	4,01	± 0,02

COMMENTS:

Recommended infill:

- quartz sand 0,3 – 1,2 mm -> 7 mm (± 10 kg/m²)

In case of free installation without mechanical fixing or bonding the turf may shrink up to 1 % due to climatic changes.

The product must be installed in compliance with the JUTAglass® Installation Guide.

According to the Regulation (EC) No 1907/2006 (REACH), this product does not contain any dangerous substances.